

MCS Series DATA SHEET

PN: 602345304, Model: C6-S7-2040-MCS-15-1000-990-SX-1G-660-3R



The Modular 3D Compact Sensor (MCS) from AT - Automation Technology is revolutionizing 3D image processing with its unique modularity, flexibility and high performance. This innovative system allows individual configuration in terms of scan width, measurement accuracy, speed, triangulation angle and working distance to perfectly match the needs of specific applications. With an unprecedented profile speed of 200 kHz and a resolution of 4096 points per profile, the MCS sets technological standards. It overcomes traditional hurdles such as high NRE costs and long development times by combining the reliability of a series product with the flexibility of a customized solution, without additional costs or minimum order quantities.

- **Freely configurable, factory-calibrated modular 3D sensors for individual solutions**
- **Five triangulation angles available (15, 20, 25, 30, 40)**
- **Four different sensor resolutions available (1280, 2040, 3070, 4090)**
- **No extra costs, long delivery times or minimum order quantities**
- **Available with different laser classes and wavelengths**



Visit our Website



Contact us



Visit our Product Documentation

AT - Automation Technology GmbH
Hermann-Bössow-Straße 6-8
23843 Bad Oldesloe

AT - Automation Technology, Inc.
380 Main Street, Suite 203
Stoneham, MA 02180

www.at-sensors.com
support@automationtechnology.de
+49 (0)4531 / 88011-42



Model Information

Model Name	C6-S7-2040-MCS-15-1000-990-SX-1G-660-3R
Part Number	602345304

General Data

Points per Profile	2048
Triangulation Angle	15 °
Working Distance	992 mm
Laser Safety Class	class3r
Laser Wavelength	660 nm
Laser Output Power	-
Laser Line Width	-
Linearity Z-Axis	0.01 % of calibrated Z-Range
Profile speed with 200-row region	1818 Hz
Maximum profile speed	43478 Hz

Field of View

	Nominal	Near Field	Far Field
Scan Width	1006.9 mm	626.8 mm	1388.6 mm
X-Resolution	491.7 µm	306.1 µm	678 µm
Z-Resolution	0 µm	-	-

Z-Range

	Full	Near Field	Far Field
Z-Range	799.5 mm	400 mm	399.5 mm

Technical Specifications

Interface	Gigabit-Ethernet (1GigE)
Inputs	Encoder A+, A-, B+, B-, Z+, Z- (TTL level) Two freely configurable digital inputs (+5 to +24 VDC)
Outputs	Two freely configurable digital outputs (+5 to +24 VDC)
Power Supply	Sensor supply +10 to +24 VDC (max. +27 VDC) Laser supply +10 to +24 VDC
Housing	Anodized aluminum IP67 certified
Environmental Conditions	Operating temperature: 0 to +40 °C Storage temperature: -20 to +80 °C Relative humidity: 20 to 80 % (non-condensing)
Vibration Resistance	Sinusoidal: DIN EN 60068-2-6:2008-10: 2g, 10-150 Hz Random: DIN EN 60068-2-64:2020-09: 7g, 10-500 Hz
Shock Resistance	DIN EN 60068-2-27: 2010-02: 15g, 3ms
Supported Standards	GenICam GigEVision
Firmware Features	RegionTracking, RegionSearch, Multiple Regions, MultiPart, AutoStart, HistoryBuffer, MultiSlope, MultiPeak
Software	SolutionPackage, MetrologyPackage, cxSDK for C, C++, .Net, Python, Matlab, Halcon

 Visit our Website

 Contact us

 Visit our Product Documentation

AT - Automation Technology GmbH
Hermann-Bössow-Straße 6-8
23843 Bad Oldesloe

AT - Automation Technology, Inc.
380 Main Street, Suite 203
Stoneham, MA 02180

www.at-sensors.com
support@automationtechnology.de
+49 (0)4531 / 88011-42